

## **ISPOFIX NEOPREN CONTACT ADHESIVE**

### DESCRIPTION

**ISPOFIX** is synthetic rubber-based, solvent-based contact adhesive, shoes and leather, furniture, printing house etc. used in the industry. It is also used in wood, paper, EVA, EPDM, neoprene and natural materials.

### FEATURES

- Very good adhesion
- Excellent bond strength
- Solvent based, rubber based
- Viscos Liquid

### INSTRUCTIONS FOR USE

The surfaces to be bonded must be dust-free, dry and clean. The adhesive is applied with the help of brushes and rollers. Before the application, surface cleaning and surface preparation processes are performed and then it is applied to both surfaces. At the end of the 10-15 minutes drying time, the parts to be bonded are combined, if the surfaces are too absorbent, two coats of adhesive can be applied. The vapor should not be inhaled, it should not come directly to the hand and eyes, and the adhesive should be used in a ventilated environment.

### CAUTION

The complete suit providing protection against chemicals, the type of protective equipment must be selected according to the concentration and quantity of hazardous substances in the particular workplace. Use in a well-ventilated area. Please review the Material Safety Data Sheet.

**This product contains Toluene.**

### PROPERTIES

Viscosity:	3500 - 3750 cps
Density:	0,860 - 0,890 g/cm <sup>3</sup>
Solid content%:	21,00 - 23,00
Color:	Transparent Yellow

## STORAGE, SHELF LIFE, PACKAGING

Store in cool place. Keep container tightly closed in a dry and well-ventilated place. Containers that are opened should be carefully closed and kept upright to prevent leakage. Shelf life: 12 months. Packaging: 200L drum.

## NOTES

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired.

Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product.

Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions.

The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.